

HEARING PROTECTION VIPER® EARMUFFS

PRODUCT DATA SHEET: EMVIP

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
EMVIP



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC_{80} 26dB.
- Hearing protection for noise levels to 110dB(A).
- Hi-vis orange for visual identification.
- General purpose use.
- Solid, lightweight ear cup construction.
- High quality ear cushions.
- Inner foam & headband cushion provides comfort during extended wear.
- Low clamping force applies minimum pressure while maintaining a tight, snug seal.
- Hygiene kits assist in extending the performance & lifetime of the earmuffs.
- 100% Metal Free - Dielectric

CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

Order replacement hygiene kit for PRO Viper Earmuffs - EMHK.

APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



ADJUSTABLE



COMFORT



HI-VIS



HYGIENIC



REUSABLE

PRODUCT DETAILS

Weight:	210g
Clamping Force:	10.8N
Colour:	Hi-Vis Orange
Size:	Standard One Size

AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
EMVIP	ORANGE	EACH	1	25

TEST DATA

ATTENUATION TABLE (ATTENUATION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	12.8	17.1	25.3	30.5	32.2	37.7	34.7
Standard Deviation	3.6	4.3	3.2	3.8	2.9	3.9	6.2
Mean-Minus-Standard Deviation Attenuations	9.2	12.8	22.1	26.7	29.1	33.8	28.5

SLC_{80} Value is 26 (Class 5)

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC_{80} 26dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS1270:2002
SMKH20580

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS