

Dräger X-dock® 5300/6300/6600 Calibration and Bump Testing

The Dräger X-dock® series provides you with full control of your portable Dräger gas detection instruments. Automatic bump tests and calibrations with reduced test gas consumption and short testing times save time and money. Comprehensive documentation and evaluations provide you with a clear overview.



As versatile as your requirements

The X-dock is available in a wide variety of versions. The X-dock 5300 includes a master station including a module for a gas detection instrument from the X-am® or Pac® family. It is immediately ready to use. The X-dock 6300 and 6600 versions can be configured freely. They consist of a master station and can be expanded with up to 10 modules for X-am and/or Pac gas detection instruments.

Easier than ever before

Insert the device, close the lid and remove it when the indicator goes "green" – a test with the X-dock is just that simple. It immediately detects all sensor combinations. Furthermore, the X-dock automatically tests and adjusts when all required test gases are connected. The station works independently and can be configured and used without a PC. The station is operated via an integrated touchscreen. A gas detection instrument is detected as soon as it is inserted, and all data is documented in the database.

More safety thanks to complete documentation

Do you need to document whether or not your devices are ready for operation? Who tested which device when, and what the result was? The X-dock stores all of the relevant data and reads the collected information from the gas detection instruments for subsequent evaluations – providing you with complete control every step of the way. In addition, you can print out a calibration or test certificate directly from the stations using a compatible printer. This functionality allows the user to manage all requirements of EN 60079-29-1 and EN 60079-29-2.

Automatically reduced costs

With a reduced gas flow (300 mL/min instead of 500 mL/min) per module, you save costs on test gases. Short testing times reduce the overall maintenance efforts. The valve concept (patent pending) requires one pump only, resulting in the need for less wear and tear parts. The valves automatically switch the test gases and – when connected – the compressed air as well.

Significant time savings

Up to 10 modules can be connected to the X-dock at any given time, allowing you to test gas detection instruments simultaneously but also independently of each other. The automatic bump test also saves time, because the test only takes 8 to 15 seconds¹. All Dräger test gas cylinders are already stored in the database – entering the part number will automatically fill in the fields required for the gas configuration. This eliminates the need for manual data entry.

¹ For standard sensors: CH₄, O₂, CO, H₂S

Benefits

Further benefits

- Touchscreen operation at the master station
- Up to three configurable test routines
- Automatic leak tests
- Automatic tests of alarm elements (acoustic, visual and vibration alarms)
- Optional charging function for X-am 1/2/5x00, 3500/8000
- Replaceable seal cartridge
- 12V operation (e.g., in vehicles) possible
- Can be subsequently expanded with up to 10 modules (X-dock 6300/6600)
- Evaluation of sensor response time

Fleet management software: Expand your possibilities

The gas detection fleet always under control! With Dräger fleet management software you network the X-dock stations for more efficiency. Your advantages:

- Evaluated data of the calibration system and the gas detection devices at a glance
- Certificates and reports, tests performed, alarms automatically documented
- Edit device configurations centrally without having to bring each device into the workshop
- E-mail notifications when inspections are necessary or intervals have expired*
- Monitor readiness and utilisation of test stations

Choose between two software solutions: X-dock® Manager or the asset licence of Gas Detection Connect

Dräger Gas Detection Connect	Dräger X-dock [®] Manager
No installation: cloud server, clients only need the internet browser	Local installation of the server and the clients necessary
Backup, updates, maintenance of the software by Dräger	Backup, maintenance, installation of updates by the user
Export user data in XLSX format or connect software via API	Export data in CSV format
Output-return module not yet available	Integrated module for dispensing and return of gas measuring instruments
GDC is the system of the future that combines asset management and live monitoring*. This system is constantly being further developed.	XDM is an established software that manages your equipment fleet with its defined functions.

^{*}The functionality is not available at the beginning. The software solution is continuously being further developed.



X-dock® 5300 X-am® 8000

X-dock® Master including X-am® 8000 module and power supply. 3 test gas connections. Limited to one module.



X-dock® 5300 X-am® 125

X-dock® Master including X-am® 125 module and power supply. 3 test gas connections. Limited to one module



X-dock® 5300 Pac®

X-dock® Master including Pac® module and power supply. 3 test gas connections. Limited to one module



X-dock® 6300 Master

3 Test gas connection. Can be expanded to 10 modules

System Components



X-dock® 6600 Master

6 Test gas connection. Can be expanded to 10 modules



X-dock® Module X-am® 8000 und X-am® 8000 (+)

Supports Dräger X-am® 3500/8000 devices



X-dock® Module X-am® 125 and X-am® 125 (+)

Supports Dräger X-am® 1/2/5x00 devices



X-dock® Module Pac®

Supports Dräger Pac® devices

System Components



X-dock® Manager Single

The X-dock® Manager is the asset management software for Dräger gas detectors. It offers the possibility to track different intervals as well as to produce test documentation and statistics reports.

The single license allows the use of an X-dock® station, e.g. in a workshop. It is unlimited in time.



X-dock® Manager Network

The network license includes the same functionality as the Single license, but any number of networked X-dock® stations can be connected.

The license is limited to one year, but can also be considered as automatic subscription with significant price advantage.



Pressure reducer

- 0.5 bar constant pressure regulator
- 0.5 bar constant pressure regulator "flow stop"
- 0.5 bar constant pressure regulator "stainless steel"



12 V car adapter supply

12 V operation available, e.g. in vehicles

System Components



3 m PVC hose with internal PTFE hose

Outer diameter: 8 mm Inner diameter: 4.7 mm



FKM hose

Solvent-resistant

Available in four lengths:

- Inner diameter 3.2 mm, length 5 m (16.4 ft)
- Inner diameter 3.2 mm, length 10 m (32.8 ft)
- Inner diameter 3.2 mm, length 20 m (65.6 ft)
- Inner diameter 3.2 mm, length 45 m (147.6 ft)



FKM adapter

10 cm



Comfort wall bracket with adjustable tilt wall mount

Easy fastening by mounting on a standard DIN rail or directly wall-mounted.



Test gas cylinder holder with test gas cylinder

For securing the test gas cylinder to the X-dock® Station.

Related Products



Dräger Bump Test Station

Easy to use, stand-alone and portable. With the Bump Test Station, functionality tests of gas detection and warning devices can be carried out easily and quickly.

Technical Data

Dräger	X-dock®	5300/	6300	6600
--------	---------	-------	------	------

	X-dock® Master	X-dock® Module	X-dock®	Module	X-dock® Module	X-dock® Module	X-dock® Module
		Pac®	X-am® 1	25	X-am® 125+	X-am® 8000	X-am® 8000+
Weight	Approx. 1,500 g	Approx. 900 g	Approx.	920 g	Approx. 960 g	Approx. 1,320 g	Approx. 1,400 g
X-dock® Master/	Approx. 120 x	Approx. 90 x 145	Approx.	90 x 145	Approx. 90 x 145	Approx. 122 x	Approx. 122 x
Module	130 x 250 mm	x 250 mm	x 250 m	m	x 250 mm	145 x 250 mm	145 x 250 mm
dimensions							
Protection class IF	P20			Yes			
Power supply				Via 24 V	['] (8321849 & 83218	350) power supply o	r car adapter
Approvals				CE marking			
Ambient condition	S	0 °C to 40 °C		40 ℃			
Gas connections							
Dräger X-dock® 53	300 / 6300			3 test ga	as inlets for connecti	ng 3 different test g	ases + one fresh air
				inlet + o	ne waste gas outlet		
Dräger X-dock® 6600		6 test gas inlets for connecting 6 different test gases + one fresh air					
				inlet + o	ne waste gas outlet		
Connections							
USB 2.0				3 USB 2	2.0 devices		
Network connection			Yes				

Ordering Information

Read	v-to-use	versions

Dräger X-dock® 5300 X-am® 8000	X-dock® Master including X-am® 8000	83 21 882	
	Module and power supply. 3 test gas		
	connections. Limited to one module.		
X-dock® 5300 X-am® 125	X-dock® Master including X-am® 125 module	83 21 880	
	and power supply. 3 test gas connections.		
	Limited to one module.		
X-dock® 5300 Pac®	X-dock® Master with Pac® module and	83 21 881	
	power supply. 3 test gas connections.		
	Limited to one module.		
Master versions			
X-dock® 6300 Master	3 test gas connections. Can be expanded to	83 21 900	
	10 modules		
X-dock® 6600 Master	6 test gas connections. Can be expanded to	83 21 901	
	10 modules		
Modular versions			
Dräger X-dock® Module X-am® 8000		83 21 893	
Dräger X-dock® Module X-am® 8000 (+)	allows charging of X-am® 8000 devices	83 21 894	
X-dock® Module X-am® 125		83 21 890	
X-dock® Module X-am® 125+	allows charging X-am® 125 devices	83 21 891	
X-dock® Module Pac®	_	83 21 892	

Ordering Information

Power supply		
24 V/1.3 A plug-in power supply	Up to 3 modules	83 21 849
24 V/5 A plug-in power supply	Up to 10 modules	83 21 850
12 V car adapter supply	Up to 5 modules	83 21 855
X-dock® Managers		
XDM Single licence (unlimited)	Unlimited license for one X-dock® station	83 28 605
XDM network license (1 year)	License for any number of connected	83 28 606
•	X-dock® stations. Valid for 1 year.	
XDM network license	License for any number of connected	83 28 607
	X-dock® stations. Automatic annual renewal.	
Accessories		
0.5 bar constant-pressure valve, nickel-		83 24 250
plated		
0.5 bar constant pressure valve, nickel-	Valve closes immediately when hose is	83 24 251
plated	removed and with flow stop	
0.5 bar constant pressure valve, stainless	Stainless steel valves are recommended in	83 24 252
steel	particular for use with Cl2 and PH3	
Hose clamp packed (5 pcs.)	for the optimized connection of pressure	83 24 095
	reducers and hoses for heavy tensile loads	
Wall mount, standard		83 21 922
Wall mount, comfort (adjustable tilt angle)		83 21 910
X-am® 8000 module seal cartridge		83 26 543
X-am® 125 module seal cartridge		83 21 986
Pac® Module seal cartridge		83 21 987
Filter for fresh air pump inlet		83 19 364
Hose FKM 5m	ideally suited to connect test gas cylinders	12 03 150
	with X-dock®	
Hose PTFE 3m		83 26 980
FKM adapter		83 24 098
Cylinder holder (table version)		83 21 918
Cylinder holder for DIN rail/wall mount		83 21 928
Outer barcode label 22 x 8 mm (500 pcs.	ideal for attaching to X-am® 125 and Pac®	AG 02551
per roll)	series clips	
Barcode scanner	CINO FBC6860LR	83 18 792

Notes

Notes

Not all products, features, or services are for sale in all countries.

Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany

www.draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA Branch Office P.O. Box 505108 Dubai, United Arab Emirates Tel +971 4 4294 600 Fax +971 4 4294 699 contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd. 61 Science Park Road The Galen #04-01 Singapore 117525 Tel +65 6872 9288 Fax +65 6259 0398 asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Indústria e Comércio Ltda. Al. Pucurui - 51 - Tamboré 06460-100 - Barueri - São Paulo Tel. +55 (11) 4689-4900 relacionamento@draeger.com

Locate your Regional Sales Representative at: www.draeger.com/contact

