



PERFORMANCE **STANDARDS**

CUT RESISTANCE RATING



TECHNOLOGIES





OEKO-TEX® CONFIDENCE IN TEXTILES TANDARD 100 TESTED FOR HARMFUL SUBSTANCES





Safety Mate demonstrates to users of our products, that they not only use industry-respected best practices but also choose to work with the organization that developed many of these standards. As a highly trusted global regulator, BSI tests products against industry recognised standards. In a world where safety is of paramount importance, BSI and its logo offer additional value and guarantees that products have been expertly tested to market-leading standards of quality, safety and durability.

SafetyMate

Why BSI Certification: By certifying with BSI,

PRODUCT DISCLAIMER: Gloves that provide cut resistance are not cut-proof. The risk for these sorts of injuries will not be completely eliminated or prevented by the use of gloves. Cut resistant gloves are not intended to provide protection against powered rotated blades or equipment, serrated or other sharp or rotating equipment. It is the responsibility of companies and/ or glove users to perform their own testing to determine the suitability for a particular application or use within the environment the gloves are to be used. Safety Mate Pty Ltd may revise this information as new information, knowledge or experience becomes available. EN407 tests are performed on the palm part of gloves only.





EXTRA HEAVY DUTY CUT LEVEL D **GLOVE FOR ANY TOUGH TASK**

NXG[™] has your hands covered. For all your extra heavy-duty work, slip into the Cut D HD for ergonomic, lightweight protection. Rated to Level D cut resistance, we assure your comfort for prolonged use. High-quality nitrile coating with innovative yarn knitting and wrapping combines to deliver all-round comfort and exceptional durability.

FEATURES

- + Heavy Duty cut resistant D glove
- + Innovative in-house NXG[™] Cut resistant yarn
- Reinforced thumb and forefinger area +
- + Excellent fit, dexterity and performance
- + 360° breathability
- + Durable and breathable nitrile coating
- + Oeko-Tex[®] 100. Sanitized[®] and dermatologically accredited

www.safetymate.com.au | info@safetymate.com.au | AUS: (07) 5582 6400 | NZ: +64 21 332 877



WILL YOUR SAFETY GLOVES ET THE NEW USTRALIAN STANDARD?

Safety Mate has always been serious about preventing hand injuries. That's why we brought a new standard of glove to the Australian market. Now Australian standards are catching up.

The new standard was published in December 2020 as AS/NZS 2161.3:2020 and key features are:

- more accurate simulation of real life cut dangers •
- an additional cut (TDM-100) rating and an optional impact rating
- Australian standards mirroring European standard EN388:2016 •

PERFORMANCE TESTS AGAINST: Old cut (co New cut (TDM) Impact

New cut (TDM) resistance levels

Level	Force to cut (Newtons/grams)	Risk*	
Х	<2 N (203g)	None	
А	≥ 2N (203g)	Low	
В	≥ 5N (509g)	Low/ Medium	
С	\geq 10N (1019g)	Medium	
D	\geq 15N (1529g)	Medium/ High	
E	≥ 22N (2243g)	High	
F	≥ 30N (3059g)	Very High	

*This is Safety Mate's opinion only. The suitability of all PPE should be risk assessed based on applications

THE NEW RATING

Test	Levels	2
Abrasion	1-4	•
Cut (Coupe Test)	1-5	•
Tear (N)	1-4	•
Puncture (N)	1-4	•
Cut (TDM-100 Test)	A-F	•
Impact protection	X or P	•

The new cut test is a game-changer for safety gloves. It will more

EN388:2016

544FP

accurately rate protection where there's a higher risk of cut injuries. This means gloves previously rated at Level 5 cut resistance may only give low to medium protection in some circumstances.

The NXG range of cut-resistant gloves already meets EN388:2016 and includes 8 Cut Level D glove styles, and 3 Cut Level F models. We're ready to assist with risk assessment and hand protection user trials to ensure your workforce are protected. Contact us to discuss the new standards and to arrange a free site glove audit and trials.

COUP TEST TDM TEST TRAVEL OF BLADE IN SINGLE DIRECTION NEW BLADE FOR EACH TEST WEIGHT (5 NEWTONS) CONDUCTIVE FABRIC SAMPLE MATERIAL SAMPLE HOLDER CURVED DEVICE HOLDER CONDUCTIVE STRIP VARIABLE FORCE (IN GRAMS) APPLIED FROM BELOW **SafetyMate**

www.safetymate.com.au | info@safetymate.com.au | AUS: (07) 5582 6400 | NZ: +64 21 332 877