

Dräger C-C550 Communication unit

Control unit for the tactical transmitter with integrated loudspeaker and microphone. Can be hooked up to a number of receiver models. Its strong and robust design is IP67 / MIL-STD-810G approved. Allows for independent deployments with the radio receiver (also without attached headset). User-friendly with two PTT buttons.



Benefits

Integrated microphone and speaker

The integrated microphone and the integrated speaker enable the use of the C-C550 without the upper unit.

Sturdy connection socket

As a sturdy and robust quick-connect socket, the C-C550 can be combined with any of the upper units allowing connection to different types of radio devices.

Robust and water-repellant

The C-C550 has been designed to be particularly sturdy and robust for many different applications as well as being watertight, complying with IP67 / MIL-STD-810G requirements.

ATEX approved

Should the system need to be used in environments where there is a potential explosion hazard, the C-C550 is designed in such a way that it meets ATEX requirements and has APEX approval.

Two large Push-To-Talk buttons

The two large push-to-talk buttons enable secure voice transmission whether the C-C550 is operated via the equipment or worn under protective clothing.

System Components



D-28795-2015

Dräger FPS®-COM 5000

Because there is no time for misunderstandings in an emergency: The Dräger FPS®-COM 5000 communication unit has been specifically developed for the full-face mask Dräger FPS® 7000 and ensures clear communication through a voice amplifier unit or radio device – even under extreme conditions.



D-28805-2015

Dräger FPS®-COM 7000

The Dräger FPS®-COM 7000 provides hands-free communication for all wearers of respiratory protection devices during a mission. Excellent voice quality is achieved by removing interfering noises.



D-28790-2015

Dräger MS-COM

The Dräger MS-COM, alternatively with swan neck microphone or with microphone positioned under the cap, can be combined with the C-C550 via stereo jack and adapted to radio units.



ST-4672-2003

Dräger HC-COM

Dräger HC-COM helmet units are compact and lightweight receiver/transmitter units which can be adapted to different helmet shapes and enable immediate, clear and reliable communication.

Technical Data

Weight	170 g (without cable connection)
Size	79 x 115 mm
Cable	4 pole Nexus PUR, flame-resistant: \varnothing 4 mm / 270 mm, spiral
Operating temperature	-40 °C to +85 °C
Protection class	IP67, MIL 810G
Intrinsic safety	depending on radio

Ordering Information

Dräger C-C550	depending on radio
---------------	--------------------

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS
Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION DACH
Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE
Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA
Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC
Dräger Singapore Pte. Ltd.
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

**REGION CENTRAL
AND SOUTH AMERICA**
Dräger Panama S. de R.L.
59 East Street, Nuevo Paitilla,
House 30, San Francisco Town
Panama City, Panama
Tel +507 377 9100
Fax +507 377 9130
servicioalcliente@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

