

Safety Data Sheet

according to the Model Work Health and Safety Regulations Date of issue:20/12/2016 Revision date:20/12/2016

Version: 1.0

SECTION 1: Identification: Product identifier and chemical identity

Product identifier 1.1.

: Mixture Product form Product name : 328 Product code : 328

Recommended uses and restrictions

Relevant identified uses : Test gas/Calibration gas. Laboratory use

Supplier information

CAC GAS & Instrumentation Pty Ltd Unit 3 36 Holbeche Rd 2148 Arndell Park - AUSTRALIA T+61 2 8676 6500

cac@cacgas.com.au - http://www.cacgas.com.au/ Emergency telephone number: 0400959760

SECTION 2: Hazards identification

Classification of the hazardous chemical

Classification (GHS-AU)

H280 Press. Gas (Comp.)

Label elements

Hazard pictograms (GHS-AU)

Hazard pictograms (GHS-AU) : GHS04 Signal word (GHS-AU) : Warning

Hazard statements (GHS-AU) : H280 - Contains gas under pressure; may explode if heated Precautionary statements (GHS-AU) : P410+P403 - Protect from sunlight. Store in a well-ventilated place

Other hazards

Other hazards not contributing to the : Asphyxiant in high concentrations.

classification

SECTION 3: Composition/information on ingredients

| Name | CAS No | Compound type | % | Classificati on according to the United Nations GHS (Rev. 4, 2011) |
|-----------------|-----------|---------------|--------|--|
| Nitrogen | 7727-37-9 | | 99.9 | Press. Gas (Comp.), H280 |
| Sulphur dioxide | 7446-09-5 | | <= 0.1 | Press. Gas (Liq.), H280 Acute Tox. 3 (Inhalation:ga s), H331 Skin Corr. 1B, H314 |

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First-aid measures after skin contact : Adverse effects not expected from this product.

21/12/2016 EN (English) 1/8

Safety Data Sheet

according to the Model Work Health and Safety Regulations

First-aid measures after eye contact

: Adverse effects not expected from this product.

First-aid measures after ingestion

: Ingestion is not considered a potential route of exposure.

4.2. Symptoms caused by exposure

Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment : None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray or fog.

Unsuitable extinguishing media : Do

: Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

General measures

: Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Act in accordance with local emergency plan. Stay upwind. Oxygen detectors should be used when asphyxiating gases may be released.

Hazardous combustion products

None.

5.3. Special protective equipment and precautions for fire-fighters

Special protective equipment for fire fighters

: In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Specific methods

Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Act in accordance with local emergency plan. Stay upwind. Oxygen detectors should be used when asphyxiating gases may be released.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Methods and material for containment and cleaning up

: Ventilate area.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.

21/12/2016 EN (English) 2/8

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Safe use of the product

: The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into atmosphere.

7.2. Conditions for safe storage, including any incompatibilities

Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

| Sulphur dioxide (7446-09-5) | | |
|-----------------------------|--------------|-----------------|
| Australia | Local name | Sulphur dioxide |
| Australia | TWA (mg/m³) | 5.2 mg/m³ |
| Australia | TWA (ppm) | 2 ppm |
| Australia | STEL (mg/m³) | 13 mg/m³ |
| Australia | STEL (ppm) | 5 ppm |

Exposure limit values for the other components

No additional information available

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

8.4. Personal protective equipment

Personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

Hand protection

Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.

Eye protection

Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications

Respiratory protection

: Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Gas filters do not protect against oxygen deficiency. Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 14387 - Gas filter(s), combined filter(s) and full face mask - EN 136. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Thermal hazard protection : None in addition to the above sections.

Environmental exposure controls

None necessary.

Other information

: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

9.1. SECTION 9: Physical and chemical properties

Physical state : Gas

21/12/2016 EN (English) 3/8

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Appearance

Molecular mass : Not applicable for gas mixtures.

Colour : Mixture contains one or more component(s) which have the following colour(s):

Colourless.

Odour : Odourless.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH : Not applicable for gases and gas mixtures.

Relative evaporation rate (butylacetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable for gases and gas mixtures.

Melting point / Freezing point : Melting point : Not applicable for gas mixtures.

Boiling point : Not applicable for gas mixtures.

Flash point : Not applicable for gases and gas mixtures.

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

Flammability (solid, gas) : No data available

Vapour pressure : Vapour pressure : Not applicable.

Vapour pressure at 50 °C : Not applicable.

Relative density : Relative vapour density at 20 °C : Not applicable.

Relative gas density: Lighter or similar to air.

Density : No data available Solubility : No data available

Log Pow : Not applicable for gas mixtures.

Viscosity : Viscosity, kinematic : Not applicable.

Viscosity, dynamic : Not applicable.

Explosive properties : Not applicable.

Oxidising properties : Not applicable.

Explosive limits : Non flammable.

Minimum ignition energy : No data available

Fat solubility : No data available

Additional information : None.

10.1. SECTION 10: Stability and reactivity

Reactivity : No reactivity hazard other than the effects described in sub-sections below. No reactivity hazard

other than the effects described in sub-sections below.

Chemical stability : Stable under normal conditions.

Conditions to avoid : Avoid moisture in installation systems.

Incompatible materials : For additional information on compatibility refer to ISO 11114.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

11.1. SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Sulphur dioxide (7446-09-5)

LC50 inhalation rat (ppm) 1260 ppm/4h

Skin corrosion/irritation : Not classified

pH: Not applicable for gases and gas mixtures.

Serious eye damage/irritation : Not classified

pH: Not applicable for gases and gas mixtures.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified

21/12/2016 EN (English) 4/8

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| Aspiration hazard | : Not classified |
|--|--|
| 328 | |
| Viscosity, dynamic | Not applicable. |
| Viscosity, kinematic | Not applicable. |
| visosony, ranomalio | тос арриоало. |
| SECTION 12: Ecological information | |
| According to the National Code of Practice for the mandatory . Information relevant for GHS classifi | Preparation of Material Safety Data Sheets , Environmental classification information is not cation is available on request |
| 12.1. Ecotoxicity | |
| Ecology - general | : Classification criteria are not met. |
| Acute aquatic toxicity | : Not classified |
| Chronic aquatic toxicity | : Not classified |
| 328 | |
| Log Kow | Not applicable for gas mixtures. |
| Log Pow | Not applicable for gas mixtures. |
| Sulphur dioxide (7446-09-5) | |
| Log Pow | Not applicable for inorganic gases. |
| Nitrogen (7727-37-9) | |
| Log Pow | Not applicable for inorganic gases. |
| 40.0 Provide Library | |
| 12.2. Persistence and degradability | |
| 328 | |
| Persistence and degradability | No data available. |
| Nitrogen (7727-37-9) | |
| Persistence and degradability | No ecological damage caused by this product. |
| 12.3. Bioaccumulative potential | |
| 328 | |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Kow | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | No data available. |
| Sulphur dioxide (7446-09-5) | |
| Log Pow | See section 12.1 on ecotoxicology |
| Nitrogen (7727-37-9) | |
| Log Pow | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | No ecological damage caused by this product. |
| 12.4. Mobility in soil | |
| 328 | |
| Ecology - soil | Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely. |
| Sulphur dioxide (7446-09-5) | |
| Log Pow | See section 12.1 on ecotoxicology |
| Nitrogen (7727-37-9) | |
| Log Pow | See section 12.1 on ecotoxicology |
| Ecology - soil | No ecological damage caused by this product. |
| 12.5. Other adverse effects | |
| | : Not classified |
| | : No known effects from this product. |
| | : None. |
| · | |
| 328 | None |
| Effect on the ozone layer | None. |
| Fluorinated greenhouse gases | False No known offcots from this product |
| GWPmix comment | No known effects from this product. |
| Sulphur dioxide (7446-09-5) | |
| Effect on global warming | No known effects from this product. |
| Fluorinated greenhouse gases | False |

21/12/2016 EN (English) 5/8

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| Nitrogen (7727-37-9) | |
|------------------------------|-------|
| Effect on the ozone layer | None. |
| Effect on global warming | None. |
| Fluorinated greenhouse gases | False |

SECTION 13: Disposal considerations

Waste treatment methods : May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Return unused product in original cylinder to supplier.

Additional information : External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1956 UN-No. (IMDG) : 1956 UN-No. (IATA) : 1956

14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : COMPRESSED GAS, N.O.S. (Nitrogen; Sulphur dioxide)

Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, n.o.s. (Nitrogen; Sulphur dioxide)

Transport by sea (IMDG) : COMPRESSED GAS, N.O.S. (Nitrogen; Sulphur dioxide)

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.2
Danger labels (ADG) : 2.2



IMDG

Transport hazard class(es) (IMDG) : 2.2
Danger labels (IMDG) : 2.2



IATA

Transport hazard class(es) (IATA) : 2.2 Hazard labels (IATA) : 2.2



14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available

21/12/2016 EN (English) 6/8

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an applicant or an emergency. Refere transporting product contains

what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by road and rail

UN-No. (ADG) : 1956
Special provision (ADG) : 274, 292
Limited quantities (ADG) : 120ml
Packing instructions (ADG) : P200

Transport by sea

UN-No. (IMDG) : 1956
Special provisions (IMDG) : 274
Limited quantities (IMDG) : 120 ml
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P200

EmS-No. (Fire) : F-C - FIRE SCHEDULE Charlie - NON-FLAMMABLE GASES

EmS-No. (Spillage) : S-V - SPILLAGE SCHEDULE Victor - GASES (NON-FLAMMABLE, NON-TOXIC)

Stowage category (IMDG) : A MFAG-No : 126

Air transport

: 1956 UN-No. (IATA) PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Forbidden PCA limited quantity max net quantity (IATA) : Forbidden PCA packing instructions (IATA) : 200 PCA max net quantity (IATA) : 75ka CAO packing instructions (IATA) : 200 CAO max net quantity (IATA) : 150kg ERG code (IATA) : 2L

14.8. Hazchem or Emergency Action Code

Hazchemcode : 2TE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

21/12/2016 EN (English) 7/8

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Abbreviations and acronyms : ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC)

No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative

STOT- SE: Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard UN - United Nations

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

IATA - International Air Transport Association

IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

WGK - Water Hazard Class

Revision date : 20/12/2016

Other information : Classification using data from databases maintained by the European Industrial Gases

Association (EIGA). Classification in accordance with calculation methods of regulation (EC)

1272/2008 CLP.

H280

Classification:

Press. Gas (Comp.)

| Full text of H-statements: | |
|-------------------------------|--|
| Acute Tox. 3 (Inhalation:gas) | Acute toxicity (inhalation:gas) Category 3 |
| Press. Gas (Comp.) | Gases under pressure : Compressed gas |
| Press. Gas (Liq.) | Gases under pressure : Liquefied gas |
| Skin Corr. 1B | Skin corrosion/irritation, Category 1B |
| H280 | Contains gas under pressure; may explode if heated |
| H314 | Causes severe skin burns and eye damage |
| H331 | Toxic if inhaled |
| | |

SDS_AU_STG

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

21/12/2016 EN (English) 8/8