

Portable Pressurised Eyewash Stations

Models: SE590A, SE591A, SE592A.

Pratt pressurised eyewash stations are ideal for applications where a conventional eyewash station or water supply is not available. The units can be used in remote locations, industrial, mining or wherever a temporary eyewash is required.

There are three model options available, each using the same 45L water capacity cylinder. The cylinder is filled on site with potable water and charged with clean compressed air to 690/700 kPa (100 psi). The eyewash on models SE590A and SE591A, is operated by push handle activation with stay open ball valves.

Model SE590A also has an additional hand-held eye and body wash spray, whereas the model SE592A only has the hand-held eye and body wash spray with squeeze trigger activation and lock on catch.

The cylinder and fittings are made of stainless steel. For both SE590A and SE591A the stainless steel eyewash assembly incorporates twin low flow spray nozzles with dust caps.



MODEL SE590A

FEATURING:

- 45L water capacity stainless steel cylinder.
- Twin eyewash assembly with low flow spray nozzles with dust caps.
- Push handle activation for eyewash.
- Stay open ball valve.
- Stainless steel eyewash assembly.
- PS920 hand-held body wash assembly with 1.2m long braided hose.
- PS920 has squeeze action trigger with lock open catch.
- Cradle bracket to mount PS920 to cylinder.
- Twin eyewash complies to AS4775.



MODEL SE591A

FEATURING:

- 45L water capacity stainless steel cylinder.
- Twin eyewash assembly with low flow spray nozzles with dust caps.
- Push handle activation for eyewash.
- Stay open ball valve.
- Stainless steel eyewash assembly.
- Twin eyewash complies to AS4775.



MODEL: SE592A

FEATURING:

- 45L water capacity stainless steel cylinder.
- PS920 hand-held body wash assembly with 1.2m long braided hose.
- PS920 has squeeze action trigger with lock open catch.
- Cradle bracket to mount PS920 to cylinder.



CYLINDER SPECIFICATIONS

FEATURING:

- Rated maximum capacity 55L.
- Actual water capacity 45L
- 304 stainless steel construction
- Twin carry handles (for use when empty).
- Pressure gauge
- Pressure relief valve
- Top fill entry point with cap
- Schrader type air filler valve
- Identification sign and instructions label.

OTHER DETAILS

FLUID: Potable water or equivalent. DO NOT USE ADDITIVES.

CHARGE WITH: Compressed air or equivalent (e.g. Nitrogen) to 690/700 kPa (100 psi).

CYLINDER WEIGHT: Dry - 14.0 kg
Filled with 45L of water – 59.0 kg

OPTIONAL ACCESSORIES

SE590TC Thermal Insulating Cover

SE590TR Hand Trolley



October 2019