

3M™ Skull Screws™ Push-to-Fit Earplugs

Technical Data Sheet

Product description

3M™ Skull Screws™ push-to fit foam earplugs offer convenience and noise attenuation with attitude. Effective hearing protection and compliance with a clean, easy twist.

Features

- Tough look of threaded metal, but feel of ultra soft foam
- Push-to-fit style means no need to touch the foam ear tip during insertion; just push the foam ear tip into the ear with the fitting stem that looks like a Phillips head screw
- Foam tips stay clean, even when your hands are dirty
- SLC_{80} 26dB (Class 5)

Applications

The 3M™ Skull Screws™ earplugs are ideal for a wide range of industrial workplace and leisure environments. Examples of typical applications include:

- Automotive
- Chemical & pharmaceutical manufacture
- Construction
- Heavy engineering
- Metal processing
- Textile manufacture
- Woodworking

Standards

These hearing protectors have been produced to comply with the requirements of the Australian /New Zealand Standard AS/NZS 1270:2002.



Materials

The following materials are used in the manufacture of this product.

Component	Material
Earplugs	Polyurethane
Cord	PVC
Fitting Stem	Thermoplastic Elastomer

Storage

Store in an area free of contamination.

Do not leave your hearing protection device in areas or locations where it can be exposed to damage or contamination.

Sunlight is particularly damaging as UV light can have a detrimental effect on the materials the product is made from.

Chemical contamination can also have a serious effect on product integrity and decontamination after use is recommended.

Use a suitable storage container especially if left in a vehicle. This will protect the hearing protection device from damage and extend its working life.

Laboratory Attenuation Values

Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean (dB)	28.1	24.5	28.1	30.1	35.3	38.5	40.0
SD (dB)	8.5	7.3	8.1	7.2	5.5	6.8	6.0
Mean - SD (dB)	19.6	17.2	20.0	22.9	29.8	31.7	34.0

SLC₈₀ 26dB (Class 5)

3M strongly recommends personal fit testing of hearing protectors. Research suggests that users may receive less noise reduction than indicated by the attenuation label value(s) on the packaging due to variation in fit, fitting skill, and motivation of the user.

Hearing protector Class 5 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise 105dB(A) to less than 110dB(A), assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.

Mean = Mean attenuation value derived from testing in accordance with AS/NZS 1270:2002.

SD = Standard Deviation derived from testing in accordance with AS/NZS 1270:2002.

Mean-SD = Mean attenuation value minus Standard Deviation
SLC80 = Single number rating commonly used in Australia and New Zealand to compare acoustic performance of hearing protectors. The subscript '80' indicates that in well managed hearing protector programs, the protection provided is expected to equal or exceed the SLC80 in 80% of protector-wearer noise spectrum combinations.

Class = A simplified process for selecting hearing protectors based on the wearers 8-hour equivalent continuous A-weighted sound pressure level.

Ordering Information

3M Order Code	Model #	Description
70071515640	P1300	3M™ Skull Screws™ Uncorded
70071515632	P1301	3M™ Skull Screws™ Corded
70071647757	393-2012-50	3M™ Skull Screws™ Probed Test Kit

WARNING! Hearing Protection Products

These hearing protectors help reduce exposure to hazardous noise and other loud sounds. Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury. For proper use, see supervisor, User instructions, or call 3M TechAssist Helpline 1800 024 46.

Important Notice: To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Australia Pty Ltd
Personal Safety Division
 Bldg A, 1 Rivett Road
 North Ryde NSW 2113

TechAssist Helpline 1800 024 464
 Customer Service 1300 363 565
 Email techassist@mmm.com
 Web www.3M.com.au/ppesafety

3M New Zealand Ltd
Personal Safety Division
 94 Apollo Drive, Rosedale
 Auckland 0632

TechAssist Helpline 0800 364 357
 Customer Service 0800 252 627
 Email 3mzntb@mmm.com
 Web www.3M.com.nz/ppesafety

3M and Skull Screws are trademarks of 3M.
 © 3M 2022. All rights reserved.
 AV