

3M™ TA560 Unvented Safety Helmet

Technical Data Sheet



Description

The Australian made 3M™ TA560 (unvented) ABS safety helmet (Type 1) with comfortable 6 point terylene head harness is the central building block providing users with a face, head and hearing certified protection system if needed. It is designed to protect wearers from numerous hazards and compliments a number of accessories.

The helmet consists of a shell and a suspension system called a harness. The shell provides the impact protection by deflecting, whilst the harness absorbs the shock and load. The transmission of force is dissipated through the shell, harness by stretching and dissipating it down through the body to the ground. The six point harness provides the cushioning by stretching and spreading the load evenly over the protected area.

The 25mm wide webbing maximises the surface area contact with the wearer's head and enhances stability/ security of the helmet.

The area between the shell and harness is the shock absorption zone and should not be treated as a storage location when worn.

Features

- ABS Type 1 safety helmet
- Australian made
- 6 point terylene harness with adjustable headband
- Replaceable Terry Towel sweatband (TA094)
- 25mm moulded slots accept all safety helmet accessories
- Polycarbonate & metal lamp bracket options available
- Ideal for general industry, construction and mining
- Certified to AS/NZS 1801:1997

Applications

Suitable for general use in industry for protection of the upper part of the wearers head.

The TA560 (unvented) safety helmet has been designed to meet the requirements of AS/NZS 1801 for shock absorption, resistance to penetration, lateral stiffness, ignition by flame and electrical insulation (electrical hazards up to 650V) when tested in the Hot (50°C), Cold (-5°C) and Wet conditions.

Type 1 safety helmets are suitable for general industry, construction and mining.



Standards

The TA560 is certified to AS/NZS 1801:1997 Type 1 ABS, for general industrial use.

The range of Safety Helmets are compatible with brand hearing, eye and face protection. Various brand PPE combinations are certified (including manufacturer's certified accessories) to Australian/New Zealand Standards.

Specifications

3M™ TA560 Unvented Safety Helmet	
Shell Material	Injection moulded ABS (plastic)
Vented or Unvented	Unvented
Harness Cradle	25mm Nylon webbing 6 point
Weight	260 g (weights differ with colours)
Harness Segments	Injection moulded HDPE (High Density Polyethylene)
Adjustment Range	50 - 66 cm
Harness Headband	Injection moulded LDPE (Low Density Polyethylene)
Harness Sweatband	Foam backed Terry Towelling (alternative: Lambswool)
Shell Colours	White, Yellow, Blue, Fluoro Orange, Fluoro Yellow, Green, Orange, Red, Watermelon, Grey

Types of Safety Helmets

The scope of AS/NZS 1801:1997 standard specifies requirement for occupational protective helmets to protect wearers heads from falling objects in building and construction, quarrying, shipbuilding, forestry, and other occupations with similar hazards. These requirements include the construction and materials of the helmet shell and head harness, mechanical strength of the shell and finish of the helmet.

In compliance with the standards objectives to specify protective helmets that are worn in a variety of occupations. brand safety helmets are classified into three types:

Type	Safety Helmet
Type 1	General industrial safety helmets
Type 2	Helmets intended for high temperature workplaces
Type 3	Helmets intended for bushfire fighting

Markings & Working Life of Safety Helmets

All information pertaining to selection, care and use is available in AS/NZS 1800:1998. Based upon industrial field tests Australian and New Zealand standards recommends, in general terms, an industrial safety helmet should be replaced every three years from date of issue, and the harness should be replaced every 2 years. Harsh conditions and/or rough usage dictate that a helmet may be replaced sooner.

Markings on safety helmets are a requirement for certification. It assists users in identifying their intended use. The shell is moulded with very important information stamped on the peak and you should familiarise yourself with the significance of this labelling.

Australian/New Zealand Standards AS/NZS 1801:1997 is an excellent reference document and provides assistance.

Replace your hard hat at regular intervals - hard hats don't last forever, even with proper care, wear and tear is inevitable, as a result AS/NZS 1800:1998 3.4 states that the average service life for a safety helmet is three years from time of issue or earlier if the helmet has changed in colour, exhibits any signs of wear or damage due to impact or deterioration.

If the sticker has not been used or removed, replace the helmet three years from the manufacture date stamp under the brim or peak of the helmet. In the centre of the stamp is the year with a directional arrow pointing to the month of the year in which the helmet was made.

Customisation & Integrity

3M's corporate branding and reflective tape options are available across the range of Australian made brand safety helmets to create and maintain company image and visibility on site.

3M's Australian made brand safety helmets are manufactured under an independently audited scheme to ISO9001. The Safety Helmets are licensed and manufactured to AS/NZS 1801:1997.

3M's logo printing and application of reflective tape to brand safety helmets does not affect the integrity of the Safety Helmet.

Maintenance/Cleaning

The safety helmet should be kept in good condition and cleaned regularly using warm water and/or a mild detergent only. A brush can be used to remove stubborn marks from the shell. Prior to washing, the harness should be removed from the shell to facilitate cleaning. The use of solvents, very hot water or harsh abrasives is not recommended.

Worn or damaged headgear parts should be replaced immediately and damaged shells (splits, cracks, dents or excessive abrasion, discolouration or weathering of the shell surface) should be discarded.

Accessories must be OEM components and never use a makeshift chinstrap. A chinstrap whilst a simple component is designed to meet specific breaking loads. This is to prevent serious accidents from occurring.

Storage

Storage is part of ongoing care and maintenance but is so often overlooked. Care should be taken to ensure your safety helmet, when not in use, is stored appropriately and not exposed to possible damage.

Refrain from leaving it sitting near the rear window of a car as it is exposed to intensified heat, sunlight and becomes a flying projectile in the event of a car accident or sudden braking.

Disposal

Most components of this assemble can be recycled. Recycle symbols are present on both the shell and harness assemblies. If recycling facilities are not available the product should be disposed of as solid waste. If the product is to be disposed of, it should be disassembled and disposed of as solid waste. Please see local authority regulations for disposal advice and locations.

Ordering Information

3M Code	Model #	Description
AT010704669	TA560:BK	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Black
AT010704909	TA560:BL	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Blue
AT010705070	TA560:FLOR	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Fluoro Orange
AT010705096	TA560:FLYE	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Fluoro Yellow
AT010705104	TA560:GN	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Green
AT010705112	TA560:GY	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Grey
AT010705138	TA560:OR	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Orange
AT010705153	TA560:RD	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Red
AT010705179	TA560:WA	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Watermelon
AT010705187	TA560:WH	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - White
AT010705195	TA560:YE	3M™ TA560 Safety Helmet ABS (Type 1) Unvented - Yellow
AT010687005	TA560RH:BL	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Ratchet headgear - Blue
AT010705476	TA560RH:WH	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Ratchet headgear - White
AT010705690	TA560RH:OR	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Ratchet headgear - Orange
AT010677360	TA560RH:RD	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Ratchet headgear - Red
AT010686999	TA560RH:WA	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Ratchet headgear - Watermelon
AT010682121	TA560RH:YE	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Ratchet headgear - Yellow
AT010705443	TA560M:WH	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - White

3M Code	Model #	Description
AT010689043	TA560M:BL	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Blue
AT010687765	TA560M:FLYE	3M™ Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Fluoro Yellow
AT010688490	TA560M:GY	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Grey
AT010705617	TA560M:OR	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Orange
AT010705435	TA560M:RD	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Red
AT010705419	TA560M:FLOR	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Fluoro Orange
AT010668443	TA560M:GN	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Green
AT010705450	TA560M:YE	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket - Yellow
AT010705401	TA560L:WH	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & poly lamp bracket - White
AT010677709	TA560L:BL	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & poly lamp bracket - Blue
AT010680281	TA560L:GN	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & poly lamp bracket - Green
AT010705385	TA560L:GY	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & poly lamp bracket - Grey
AT010705559	TA560L:OR	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & poly lamp bracket - Orange
AT010685983	TA560L:RD	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & poly lamp bracket - Red
AT010671348	TA560L:YE	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & poly lamp bracket - Yellow
AT010705484	TA560RT:WH	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Style 1 reflective tape - White

3M Code	Model #	Description
AT010667288	TA560RT2:BL	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Style 2 reflective tape - Blue
AT010705534	TA560RT2:FLOR	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Style 2 reflective tape - Fluoro Orange
AT010705567	TA560RT2:FLYE	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Style 2 reflective tape -Fluoro Yellow
AT010705609	TA560RT2:WH	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Style 2 reflective tape - White
AT010705625	TA560RT2:YE	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & Style 2 reflective tape - Yellow
AT010688334	TA560MRH:WH	3M™ TA560 Safety Helmet ABS (Type 1) Unvented & metal lamp bracket, cable clip & ratchet headgear - White

Attachments & Accessories

3M Code	Model #	Description
AT010700691	TA094	Replacement Sweatband Terry Towelling
AT010701343	TA095	Replacement Sweatband Lambswool
AT010707381	VH500	Nylon Visor Holder for TA500 Helmet Visor
AT010707399	VH500P	Nylon Peaked Visor Holder for TA500
AT010659731	VV765	Aluminium Visor Holder For TA500 Series Helmets
AT010700006	2010892	Visor Post L Profile T25 GRP
AT010655499	KF010	Visor Holder HC600 HC71
AT010655481	KF003	Visor Holder To Suit HC600 71
AT010659509	TA179	Balaclava for use under Helmet
AT010659491	TA177:NA	Wide Brim Neck Flap Earmuff Compatible
AT010659426	TA173:BK	Canvas Brim and Neck Flap - Black

3M Code	Model #	Description
AT010659434	TA173:GN	Canvas Brim and Neck Flap - Green
AT010659459	TA173:OR	Canvas Brim and Neck Flap - Orange
AT010659467	TA173:RD	Canvas Brim and Neck Flap - Red
AT010659475	TA173:WH	Canvas Brim and Neck Flap - White
AT010659483	TA173:YE	Canvas Brim and Neck Flap - Yellow
AT010659442	TA173:NA	Canvas Brim and Neck Flap - Navy
AT010659418	TA170	Cotton Neck Flap White
AT010703992	TA175	Chinstrap for TA500 & TA400 Series Helmets
AT010704065	TA180	Reflective Tape Kit for Helmets
AT010706714	TA597	Replacement 6 Point Harness for TA500 Series
AT010706730	TA598	Ratchet Headgear for TA500 Series Helmet
AT010700196	HXSC71	Insert Slot Cover for TA500 Series Helmets

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Australia Pty Ltd
Personal Safety Division
 Bldg A, 1 Rivett Road
 North Ryde NSW 2113
 TechAssist Helpline: 1800 024 464
 Customer Service: 1300 363 565
 Email: techassist@mmm.com
 Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
 94 Apollo Drive, Rosedale
 Auckland 0632
 TechAssist Helpline: 0800 364 357
 Customer Service: 0800 252 627
 Email: techassist@mmm.com
 Web: www.3M.com/nz/ppesafety

3M is a trademark of 3M Company.
 Please recycle. Printed in Australia.
 © 3M 2018. All rights reserved.
 AV011472477